

● INTRODUCING

Spark S-302

Ethernet IP video intercom kit — indoor monitor + outdoor station.

Everything you need in one box. The S-302 pairs a 7-inch IPS touchscreen indoor monitor with a 3.0 MP outdoor station — IC card access, infrared night vision, full-duplex audio and Tuya smart-home control, all over a standard Ethernet network.



● 7" IPS touchscreen

● 3.0 MP outdoor camera

● 140° wide angle

● IC card access

● IR night vision

● Ethernet / PoE

● IP65 outdoor

● Tuya smart-home

● INCOMING CALL

Someone's at the door. You're already there.

The outdoor station's call button rings the indoor monitor instantly. See the visitor in FHD 1080P, talk in full-duplex and unlock with a tap — all from the 7-inch touchscreen.



Full-duplex audio

Talk and listen simultaneously — natural two-way conversation, no delays.



Relay unlock

Unlock the door directly from the call screen with one tap.



Snapshot & record

Save a JPG photo or a video clip to the 128 GB SD card during the call.



IC card access

Residents can present an IC card to the outdoor station to unlock without calling.



IR night vision

The outdoor station's infrared illumination activates automatically after dark.



IP65 outdoor

Aluminium alloy outdoor station rated IP65 — dust-tight and rain-resistant.

● OUTDOOR STATION

Sees more. Keeps the weather out.

The S-301 outdoor station is built from aluminium alloy and rated IP65. Its 3.0 MP camera covers 140° and switches to infrared night vision automatically — so you always see who's there, rain or shine.

**01 3.0 MP camera**

FHD 1080P video decoded in H.264 — sharp, detailed image at any time of day.

02 140° wide angle

Wide 140° lens captures the full entrance — no blind corners.

03 IR night vision

Infrared illumination switches on automatically for clear images after dark.

04 IP65 rated

Dust-tight and water-resistant — rated for all outdoor conditions.

05 IC card access

Built-in card reader supports standard IC cards for keyless entry.

06 Aluminium alloy body

140 × 60 × 25 mm. Compact, robust and tamper-resistant.

● INDOOR MONITOR

Vivid 7-inch panel. Everything at a touch.

The indoor monitor's 7-inch IPS touchscreen displays visitors in crisp 1024 × 600 resolution. Physical answer and unlock buttons on the side panel let you respond without even looking at the screen.

01 7" IPS touchscreen

1024 × 600 IPS display — wide viewing angles and vivid colours.

02 FHD 1080P input

Receives H.264 FHD 1080P video from the outdoor station.

03 Full-duplex audio

8 Ω 2 W speaker with -40 dB microphone — talk and listen simultaneously.

04 Side-panel buttons

Physical answer and unlock buttons for fast, tactile response without touching the screen.

05 Snapshot & record

Save JPG snapshots or video to a 128 GB SD card directly from the call screen.

06 Tuya app control

Receive calls, view the camera and unlock remotely from the Tuya or SmartLife app.



● TUYA ECOSYSTEM

Connected to every corner of your home.

The S-301 pairs with the Tuya and SmartLife apps over Wi-Fi. Receive door calls on your smartphone, view the live camera feed and unlock the door — from anywhere in the world.



Tuya / SmartLife

Native Tuya support — pair with the SmartLife app for remote access.



Remote viewing

View the live outdoor camera feed from anywhere via the Tuya app.



PoE powered

One CAT5/5e cable carries both data and power to both units.

01 Remote door calls

When the outdoor station rings, your phone rings too — answer and unlock from anywhere.

02 Live monitoring

Open the Tuya app any time to view the outdoor station's live camera feed.

03 PoE or DC 24 V

Power the kit from a PoE switch or a DC 24 V supply — whichever suits your installation.



● SETUP

One cable. Both devices. Up and running in minutes.

Connect the indoor monitor and outdoor station with a single UTP CAT5/CAT5e cable. Power from a PoE switch or DC 24 V supply. Both units mount to any flat surface with the included hardware.

01 Cable: CAT5 / CAT5e

UTP CAT5/CAT5e from outdoor station to indoor monitor — maximum 50 m run.

02 Lock cable: RVV2×1.0

Connect the relay lock with RVV2×1.0 cable, up to 10 m.

03 Power: PoE or DC 24 V

Indoor unit: DC 24 V / PoE. Outdoor unit: DC 24 V / 200 mA via indoor unit or PoE.

04 Surface mount — both units

Wall brackets and all fixings included. Mount to any flat surface indoors or outdoors.

05 Motor lock support

Relay output supports one motor-operated electric lock (12 V, max 500 mA instantaneous).

06 What's in the box

Indoor monitor · Outdoor station · Wall brackets · CAT5 terminals · IC cards ×2 · Screws & anchors · User manual

● SPECIFICATIONS

Spark S-302

Ethernet IP video intercom kit · indoor monitor + outdoor station

INDOOR MONITOR

Screen	7" IPS, touchscreen
Resolution	1024 × 600
Video input	FHD 1080P
Video codec	H.264
Speaker	8 Ω, 2 W
Intercom mode	Full-duplex
SD card	Up to 128 GB
Platform	Tuya / SmartLife
Power	DC 24 V / PoE
Standby power	≤ 2 W
Working temp.	−30 °C to +50 °C
Installation	Surface mount

OUTDOOR STATION

Camera	3.0 MP HD
Video	FHD 1080P, H.264
Viewing angle	140°
Night vision	Infrared
Access control	IC card
Body	Aluminium alloy
Dimensions	140 × 60 × 25 mm
Protection	IP65
Power	DC 24 V / 200 mA
Standby power	≤ 2.4 W
Working temp.	−30 °C to +50 °C
Installation	Surface mount